

TOP

TOP

ZLINE
ATTAINABLE LUXURY®

TOP



7 1/4"
(185 mm)

1 7/8"
(47 mm)

2 1/4"
(58 mm)

6 5/16"
(160 mm)

6 5/16"
(160 mm)

6 5/16"
(160 mm)

6 5/16"
(160 mm)

2 1/4"
(58 mm)

24 1/16"
(610.5 mm)

24 1/16"
(610.5 mm)

COLUMN REFRIGERATION
RBCRV-30 MODELS

Recommended Door Thickness
Minimum: 3/4" (19 mm)
Maximum for Flush Inset: 15/16" (24 mm)

Door Height
79 15/16" (2030 mm)

1 1/16"
(18 mm)

1 1/16"
(27.2 mm)

1 1/16"
(18 mm)

1 1/16"
(27.2 mm)

1 1/16"
(18 mm)

1 1/16"
(27.2 mm)

1 1/16"
(18 mm)

1 1/16"
(27.2 mm)

27 3/16"
(690.5 mm)

27 3/16"
(690.5 mm)

2 1/4"
(58 mm)

6 5/16"
(160 mm)

6 5/16"
(160 mm)

6 5/16"
(160 mm)

6 5/16"
(160 mm)

2 1/4"
(58 mm)

1 7/8"
(47 mm)

7 1/4"
(185 mm)

BOTTOM



BOTTOM

1.0.0

BOTTOM